ATV / 3 WHEELER

ITEM NUMBER	TIRE SIZE	TREAD Pattern	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUND COMPARISON SOFT TO FIRM	APPLICATION
11940	12.0x 8.0-6	Treaded Crossblock	8.0″	12.0″	37.5″	9-10″	10″	9.75″	D10A, D20A, D30A	Youth ATV Rear
11960	12.0x 9.0-6	Treaded Crossblock	9.0″	12.0″	38.5″	9-10"	10″	10.25″	D10A, D20A, D30A	Youth ATV Rear
16050	16.0x 8.5-8	Small Crossblock	8.5"	16.0"	53.5"	8-9"	9″	10.5″	T30	3 Wheeler
16105	21.0x 6.0-10	Rib	7.0″	21.0″	66.0″	6-8″	7	8.25″	T20	3 Wheeler Front
16110	18.0x11.0-10	Wide Tri-Trac	10.0"	18.0"	57.0"	10″	10″	11.0″	T10, T20	Flat Track & TT
16115	18.0x10.0-10	Tri-Trac	9.0″	18.0″	57.0″	9-10"	9″	10.5	RD20, RD30	Flat Track & TT
16130	18.5x 6.0-10	Tri-Trac Front	6.0″	18.5″	59.0″	5″	5″	7.5″	T10	Flat Track & TT
16250	18.0x 5.5-10	ATV Front	5.5″	18.0″	57-58″	5″	5″	6.6″	D10, D12,RD20, RD30	Flat Track & TT
16275	18.5x 8.0-10	Large Crossblock	8.5"	18.5″	59.0″	8″	8″	9.5″	D12	Flat Track & TT
16300	18.0x10.0-10	Large Crossblock	10.0″	18.0″	58.0″	9-10"	10″	11.0″	D12, RD12, RD15, RD20, RD30	Flat Track & TT
16325	18.5x10.0-10	Large Crossblock	10.0"	18.5"	59.0″	10″	10″	10.9″	D10, RD12, RD15	Flat Track & TT
16600	20.5x 6.0-10	MX Front	5.0″	20.5"	63.25"	5″	5″	6.5″	MX 150	MX Front
16700	18.0x10.0-8	MX Rear	8.5"	18.0"	56.5"	8″	8″	9.625"	MX 150, MX200	MX Rear
16800	21.0x 7.0-10	MX Mud Front	6.0″	21.0"	57.5″	5″	5″	6.25″	XC200	MX Mud Front
16900	20.0x11.0-9	MX Mud Rear	9.75"	20.0"	62.5"	8″	8″	10.75"	XC200	MX Mud Rear
42400	15.0/ 6.0-8	ATV Front	6.0″	15.0″	49.0″	6″	6″	7.4″	D12, RD20	Flat Track & TT
42450	15.0/ 7.0-8	Small Crossblock	7.0″	15.0″	49.0"	6″	6″	7.5″	RD20	Flat Track & TT
42500	15.0/ 8.0-8	Small Crossblock	8.0″	15.0″	49.5″	7″	7″	8.5″	RD20	Flat Track & TT
42550	16.0/ 8.5-8	Small Crossblock	8.5"	16.0″	53.5″	9″	9″	10.5″	RD20	Flat Track & TT

UTV / SxS

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC. I	RECOM. RIM WIDTH	MEASURED RIM WIDTH	SECTION WIDTH	COMPOUND COMPARISON SOFT TO FIRM	APPLICATION
16105	21.0x6.0-10	RIB	7.0″	21.0″	66.0″	6-8"	7″	8.25″	H500	RZR 170
16400	27.5/8.0-15	Super Chain Link	8.0″	27.75"	87.0"	7-8"	8″	10.5″	S500, M500	Prod 1000/PS
16450	27.5/8.0-15	Super Chain Link	8.75″	27.75"	87.0″	7-9"	8″	11.3″	S500, M500	Turbo 1000/PM
S0FT										FIRM
-	D10	RD12		D12	RD15	RD20	RD30			
	D10A				S500	D20A	D30A M50	0		
						T10	T20	MX150	MX200 T30	

WARNING: Not For recreational use. Hoosier ATV Tires are designed and manufactured for racing purpose only. Within a Closed course for organized competitions. The prohibited use of Hoosier Racing tires on public roadways may result in loss of traction, unexpected loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible **SERIOUS PERSONAL INJURY OR DEATH.**

